



| SIZE | XS | S | M | L | XL | XXL |
|----------------------|-------|-------|-------|-------|-------|--------|
| A | 480 | 500 | 530 | 550 | 580 | 610 |
| A² | 440 | 460 | 490 | 510 | 540 | 565 |
| B | 505 | 525 | 540 | 560 | 575 | 590 |
| C | 74.5° | 73.5° | 73.5° | 73° | 72.5° | 72.5° |
| D | 120 | 125 | 145 | 160 | 180 | 195 |
| E | 72° | 72° | 72.5° | 72.5° | 73° | 73° |
| F | 70 | 68 | 68 | 68 | 66 | 66 |
| G | 560 | 571,3 | 582,5 | 597,3 | 603,5 | 618,3 |
| H | 402 | 402 | 402 | 402 | 402 | 402 |
| I | 951,5 | 963,5 | 974,7 | 990,1 | 996,4 | 1011,3 |
| J | 48 | 48 | 48 | 48 | 48 | 48 |
| K | 721,7 | 738,9 | 765,8 | 777,2 | 812,3 | 834 |
| L | 133,3 | 143,2 | 149,3 | 158,7 | 169,3 | 173,9 |
| P* | 1110 | 1140 | 1170 | 1200 | 1230 | 1270 |
| O* | 350 | 360 | 365 | 370 | 375 | 380 |

* WEIGHT TOLERANCES: FRAME AND FORK ± 5%

A Seat tube total length • **A²** Seat tube joint • **B** Top tube length • **C** Seat tube angle • **D** Head tube • **E** Head tube angle • **F** BB drop • **G** BB to front wheel • **H** Chain stay • **I** Wheelbase • **J** Fork rake • **K** Standover height • **L** Standover height offset • **P** Frame weight (gr) • **O** Fork weight (gr)